Sprayway®

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 203-003

Product name Rubber Cleaner & Rejuvenator

Effective date 12-Feb-2010
Company information Sprayway, Inc. 1005 Westgate

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 **Emergency telephone outside US** 703-527-3887

Version # 07

Supersedes date 10-Aug-2009

2. Hazards Identification

Emergency overview FLAMMABLE

Aerosol. CONTENTS UNDER PRESSURE.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Prolonged

exposure may cause chronic effects.

Potential health effects

Eyes Contact may irritate or burn eyes.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effectsConjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss

of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis. Defatting

of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Light Aliphatic Solvent Naphtha	64742-89-8	30 - 40
Propylene Glycol Monomethyl Ether	107-98-2	20 - 30
2-Methyl-2,4-Pentanediol	107-41-5	15 - 20
Dipropylene Glycol Methyl Ether	34590-94-8	10 - 15
Isopropyl Alcohol	67-63-0	8 - 10
Carbon Dioxide	124-38-9	3 - 5
Non-hazardous and other components below reportable levels		0.1 - 1

4. First Aid Measures

First aid procedures

Eye contact Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and

persists.

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Product name: Rubber Cleaner & Rejuvenator Product #: 203 Rubber Cleaner & Rejuvenator

Ingestion

Rinse mouth thoroughly. Get medical attention immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Heat may cause the containers to explode. Runoff to sewer may cause fire or explosion hazard

Extinguishing media

Suitable extinguishing media

Water fog. Alcohol foam. Dry chemical. Polymer foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water.

Protection of firefighters

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Propylene Glycol Monomethyl Ether	107-98-2	100 ppm	150 ppm	Not established
2-Methyl-2,4-Pentanediol	107-41-5	Not established	Not established	25 ppm
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm	150 ppm	Not established
Isopropyl Alcohol	67-63-0	200 ppm	400 ppm	Not established
Carbon Dioxide	124-38-9	5000 ppm	30000 ppm	Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm	Not established	Not established
Isopropyl Alcohol	67-63-0	400 ppm	Not established	Not established
Carbon Dioxide	124-38-9	5000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Do not get in eyes. Chemical goggles are recommended.

Wear appropriate chemical resistant clothing. Chemical resistant gloves. Skin protection

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators. If permissible levels are exceeded use NIOSH

mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Compressed liquefied gas. **Appearance Boiling point** 267.8 °F (131.1 °C) estimated

Color clear colorless

Flammability (HOC) 33.775 kJ/g estimated

Flash back

Flash point 53 °F (11.7 °C) Concentrate

Form Aerosol. Odor Characteristic. рН Not applicable

Physical state Liquid.

80 - 100 psig @ 70F **Pressure**

Solubility Partially 0.84 Specific gravity

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions. Risk of ignition.

Heat, flames and sparks. Conditions to avoid

Isocyanates. Strong oxidizing agents. Incompatible materials Hazardous decomposition products May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LD50: 6060 mg/kg estimated, Rat, Dermal

Acute LC50: 198 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

2-Methyl-2,4-Pentanediol 107-41-5 Inhalation LC50 Rat >310 mg/m3 1 h; Oral LD50 Rat 3692 mg/kg; Dermal LD50

Rabbit 8560 µL/kg

34590-94-8 Dipropylene Glycol Methyl Ether Oral LD50 Rat 5230 mg/kg; Dermal LD50 Rabbit 9500 mg/kg

Isopropyl Alcohol Inhalation LC50 Rat 72.6 mg/L 4 h; Oral LD50 Rat 4396 mg/kg; Dermal LD50 Rat 67-63-0

12800 mg/kg; Dermal LD50 Rabbit 12870 mg/kg

Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg Light Aliphatic Solvent Naphtha 64742-89-8

Inhalation LC50 Rat 54.6 mg/L 4 h; Inhalation LC50 Rat >24 mg/L 1 h; Oral LD50 Ra Propylene Glycol Monomethyl 107-98-2

Ether 5200 mg/kg; Dermal LD50 Rabbit 13000 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by OSHA criteria. **Teratogenicity**

12. Ecological Information

LC50 21647 mg/L estimated, Fish, 96.00 Hours, **Ecotoxicity**

> EC50 15252 mg/L estimated, Daphnia, 48.00 Hours, IC50 5751 mg/L estimated, Algae, 72.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

13. Disposal Considerations

Disposal instructions

Contents under pressure. Do not puncture, incinerate or crush. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions156, 306Packaging non bulk156, 306Packaging bulkNone

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1UN number1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the

OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Dipropylene Glycol Methyl Ether 34590-94-8 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3,

R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or

sulfonate, Chemical Category N230)

Isopropyl Alcohol 67-63-0 1.0 % de minimis concentration (only if manufactured by the strong acid process, no

supplier notification)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

None

Product name: Rubber Cleaner & Rejuvenator Product #: 203 Rubber Cleaner & Rejuvenator

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
A 10 / 11 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1		

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

107-41-5 2-Methyl-2,4-Pentanediol Present Carbon Dioxide 124-38-9 Present Dipropylene Glycol Methyl Ether 34590-94-8 Present

Isopropyl Alcohol 67-63-0 Environmental hazard

Light Aliphatic Solvent Naphtha 64742-89-8 Present Propylene Glycol Monomethyl 107-98-2 Present

Ether

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1*

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

MSDS sections updated This document has undergone significant changes and should be reviewed in its entirety.

Prepared by Regulatory Compliance